

PERFORMANCE DATA:

MICRON RATING.....	5 NOMINAL
COLLAPSE PRESSURE RATING.....	75 PSID
MAXIMUM TEMPERATURE.....	250 F
DIRECTION OF FLOW.....	OUTSIDE->IN

DIMENSIONAL DATA:

(A) OUTER DIAMETER, TOP.....	6.00"
(B) OUTER DIAMETER, BOTTOM.....	6.00"
(C) INNER DIAMETER, TOP.....	2.63"
(D) INNER DIAMETER, BOTTOM.....	2.63"
(E) LENGTH.....	36.00"
(F) THREAD.....	NONE

PHYSICAL DATA:

SEAL MATERIAL.....	BUNA-N
TYPE OF ADHESIVE.....	POLYVINYLCHLORIDE
TYPE OF ENDCAP.....	PLATED STEEL
CENTERTUBE.....	PLATED STEEL
TYPE OF MEDIA.....	PAPER
FILTER AREA.....	68 SQ.FT.
PLATING.....	ELECTROTIN PLATED
OUTER JACKET.....	YES
CONFIGURATION.....	DOUBLE OPEN END

PACKAGING DATA:

NUMBER PER CARTON.....	6
WEIGHT OF CARTON.....	40.00 pounds

NOTE 1: RECOMMENDED CHANGEOUT DIFFERENTIAL PRESSURE = 20 PSID