

PERFORMANCE DATA:

| | |
|------------------------|-------------|
| MICRON RATING..... | 3 |
| BETA RATING..... | N/A |
| DIRECTION OF FLOW..... | OUTSIDE->IN |

DIMENSIONAL DATA:

| | |
|---------------------------------|-----------|
| (A) OUTER DIAMETER, TOP..... | 3.70" |
| (B) OUTER DIAMETER, BOTTOM..... | 3.70" |
| (C) INNER DIAMETER, TOP..... | 0.00 |
| (D) INNER DIAMETER, BOTTOM..... | 0.00 |
| (E) LENGTH..... | 5.25" |
| (F) THREAD..... | 1"-12 UNF |

PHYSICAL DATA:

| | |
|-----------------------|-------------------|
| HANDLE..... | NONE |
| SEAL MATERIAL..... | BUNA-N |
| TYPE OF ADHESIVE..... | EPOXY |
| TYPE OF ENDCAP..... | PLATED STEEL |
| CENTERTUBE..... | STEEL |
| TYPE OF MEDIA..... | MICROGLASS |
| PLATING..... | ELECTROTIN PLATED |
| OUTER JACKET..... | YES |

PACKAGING DATA:

| | |
|------------------------|-------|
| NUMBER PER CARTON..... | 12 |
| WEIGHT OF CARTON..... | 23.00 |

NOTE 1: RECOMMENDED CHANGEOUT DIFFERENTIAL PRESSURE = 20 PSID