

PERFORMANCE DATA:

|                               |             |
|-------------------------------|-------------|
| MICRON RATING.....            | 12 ABSOLUTE |
| BETA RATING.....              | B12 = 200   |
| COLLAPSE PRESSURE RATING..... | 150 PSID    |
| MAXIMUM TEMPERATURE.....      | 250 F       |
| DIRECTION OF FLOW.....        | OUTSIDE->IN |

DIMENSIONAL DATA:

|                                 |       |
|---------------------------------|-------|
| (A) OUTER DIAMETER, TOP.....    | 3.10" |
| (B) OUTER DIAMETER, BOTTOM..... | 3.10" |
| (C) INNER DIAMETER, TOP.....    | 1.72" |
| (D) INNER DIAMETER, BOTTOM..... | 0.00  |
| (E) LENGTH.....                 | 8.30" |

PHYSICAL DATA:

|                       |                 |
|-----------------------|-----------------|
| SEAL MATERIAL.....    | BUNA-N          |
| TYPE OF ADHESIVE..... | EPOXY           |
| TYPE OF ENDCAP.....   | PLATED STEEL    |
| CENTERTUBE.....       | PLATED STEEL    |
| TYPE OF MEDIA.....    | MICROGLASS      |
| PLATING.....          | ZINC PLATED     |
| OUTER JACKET.....     | NONE            |
| CONFIGURATION.....    | SINGLE OPEN END |

PACKAGING DATA:

|                        |            |
|------------------------|------------|
| NUMBER PER CARTON..... | 1          |
| WEIGHT OF CARTON.....  | 4.0 POUNDS |

NOTE 1: RECOMMENDED CHANGEOUT DIFFERENTIAL PRESSURE = 50 PSID