

PERFORMANCE DATA:

MICRON RATING.....	12 ABSOLUTE
BETA RATING.....	B12 = 200
COLLAPSE PRESSURE RATING.....	150 PSID
MAXIMUM TEMPERATURE.....	250 F
DIRECTION OF FLOW.....	OUTSIDE->IN

DIMENSIONAL DATA:

(A) OUTER DIAMETER, TOP.....	3.10"
(B) OUTER DIAMETER, BOTTOM.....	3.10"
(C) INNER DIAMETER, TOP.....	1.72"
(D) INNER DIAMETER, BOTTOM.....	0.00
(E) LENGTH.....	8.30"

PHYSICAL DATA:

SEAL MATERIAL.....	BUNA-N
TYPE OF ADHESIVE.....	EPOXY
TYPE OF ENDCAP.....	PLATED STEEL
CENTERTUBE.....	PLATED STEEL
TYPE OF MEDIA.....	MICROGLASS
PLATING.....	ZINC PLATED
OUTER JACKET.....	NONE
CONFIGURATION.....	SINGLE OPEN END

PACKAGING DATA:

NUMBER PER CARTON.....	1
WEIGHT OF CARTON.....	4.0 POUNDS

NOTE 1: RECOMMENDED CHANGEOUT DIFFERENTIAL PRESSURE = 50 PSID