

Application

For use in Peerless Manufacturing, Perry Equipment and King Tool type filter-separators and dry gas filters that use the nominal 4-1/2 inch O.D. by 36 inch long element, flowing from the outside to the inside.

Technical

The Permian PFG-336 series elements have the following features:

- The Permian PFG-336 series elements are efficient filter-coalescer elements. The molded fiberglass tube is constructed of graded glass fibers, compressed to the proper density and bonded with inert phenolic binders.
- The fiberglass tube is supported with a heavy-duty, spiral locked center core for superior resistance to collapse due to high differential pressure. The center core can withstand over 75 PSI differential pressure without collapsing.
- The metal end caps are mechanically attached to the center core for structural strength. The fiberglass media is attached to the endcaps with a highly resistant adhesive to prevent any possibility of by-pass.
- Buna N gaskets are attached to the end caps with a polyurethane adhesive and go through a special heat treatment. The adhesive is resistant to all hydrocarbons.
- The standard Permian PFG-336 series filter element will remove particles down to one micron without excessive differential pressure build-up.
- A cotton outer wrap protects the fiberglass from dirt and damage during shipment and protects the operator during element change-out.
- The Permian PFG-336 is, primarily, designed as a replacement for PECO Model FG-336 elements and are dimensionally identical.

Performance and operating data

Nominal micron ratings available	10, 5, 1
Recommended maximum operating temperature	275° F
Recommended maximum change-out differential	15 PSI
Gasket material	Buna N

About Gardner & Clark, Inc.

Gardner & Clark, Inc. can design and manufacture many different filtration products to help you solve your specific problem. We invite your inquiries to custom design and manufacture a filter cartridge for your specific need.

All data and statements concerning our products indicate representative properties and characteristics obtainable. But we make no warranty, express or implied, concerning their use, and we accept no responsibility for misapplication of these products, or their use under any conditions.