

## Application

Permian's PMK-336 series pleated elements are specially designed to replace 336 style sock elements in filter cases using a compression plate for a sealing mechanism. The media is designed for use in natural gas contact solvents and well completion fluids where especially fine filtration is desired.

## Characteristics

Permian's pleated paper PMK-336 elements have the following characteristics:

- Beta ratios up to 1000 at rated efficiency
- >25 square feet of surface area
- Robust construction. Over 100 PSI collapse pressure.
- Large dirt holding capacity.
- Highest quality components.

## Specifications

Length .....	36.75 inches
Outside diameter .....	3 inches
Inside diameter .....	1.5 inches
Center core .....	Carbon steel
End caps .....	Carbon steel
Sealing mechanism .....	Coiled spring
Gaskets .....	Buna N
Outer cover .....	Polypropylene mesh
Media .....	Cellulose/synthetic blended paper
Operating temp. range .....	-60° to +250°
Available ratings .....	1, 2, 5, 10, 25, 40, 70 micron, absolute

## Recommended operating limits

Initial pressure drop .....	< 2 PSI
Recommended charge-out Delta P .....	15 PSI
Maximum flow, irrespective of differential pressure .....	12 U.S.G.P.M.
Maximum element operating life irrespective of differential pressure .....	1 year