

ABSOLUTE RATED PLEATED PAPER ELEMENTS

Permian's absolute rated PPMK-4340 elements have the following characteristics:

Beta ratios up to 1000 at rated efficiency.

>44 square feet of surface area.

Robust construction. Over 100 PSI collapse pressure.

Large dirt holding capacity.

Highest quality components.

SPECIFICATIONS

LENGTH.....	38-5/8 INCHES
OUTSIDE DIAMETER.....	3-3/4 INCHES
INSIDE DIAMETER.....	1-7/8 INCHES
CENTER CORE.....	CARBON STEEL
END CAPS.....	CARBON STEEL
SEALING MECHANISM.....	O'RING & RETAINER
ORING.....	BUNA N
OUTER COVER.....	PLASTIC MESH
MEDIA.....	CELLULOSE/SYNTHETIC BLEND
OPERATING TEMPERATURE RANGE.....	-60 TO +200°F
AVAILABLE RATINGS.....	2, 5, 10, 20 & 40 MICRONS, ABSOLUTE

RECOMMENDED OPERATING LIMITS

INITIAL PRESSURE DROP.....	< 2 PSI
RECOMMENDED CHANGE-OUT DELTA P.....	15 PSI
MAXIMUM FLOW, IRRESPECTIVE OF DIFFERENTIAL PRESSURE.....	62 U.S.G.P.M.
MAXIMUM ELEMENT OPERATING LIFE IRRESPECTIVE OF DIFFERENTIAL PRESSURE.....	1 YEAR