

CHARACTERISTICS

Permian's pleated PPMP-2530-30AB-D elements have the following characteristics:

- Beta ratios up to 5000 at rated efficiency
- Greater than 18 square feet of surface area
- Robust construction. Over 100 PSI collapse pressure at 80°F.
- Large dirt holding capacity.
- Highest quality components.
- No adhesive.

SPECIFICATIONS

LENGTH.....	30.00 INCHES
OUTSIDE DIAMETER.....	2.5 INCHES
INSIDE DIAMETER.....	1.06 INCHES
CENTER CORE.....	POLYPROPYLENE
END CAPS.....	POLYPROPYLENE
MEDIA.....	POLYPROPYLENE
STANDARD GASKETS.....	BUNA N
OPERATING TEMPERATURE RANGE.....	-60 TO +180°F
MICRON RATING.....	30

RECOMMENDED OPERATING LIMITS

INITIAL PRESSURE DROP.....	< 2 PSI
RECOMMENDED CHANGE-OUT DELTA P.....	15 PSI
MAXIMUM FLOW, IRRESPECTIVE OF DIFFERENTIAL PRESSURE.....	24 U.S.G.P.M.
MAXIMUM ELEMENT OPERATING LIFE IRRESPECTIVE OF DIFFERENTIAL PRESSURE.....	1 YEAR