

Permian's absolute rated pleated PPMP-4536 elements have the following characteristics:

1. Beta ratios up to 5000 at rated efficiency
2. >24 square feet of surface area
3. Robust construction. Over 75 PSI collapse pressure.
4. Large dirt holding capacity.
5. Highest quality components.

### **SPECIFICATIONS**

LENGTH.....	36 INCHES
OUTSIDE DIAMETER.....	4.5 INCHES
INSIDE DIAMETER.....	3.1 INCHES
CENTER CORE.....	CARBON STEEL
END CAPS.....	CARBON STEEL
GASKETS.....	BUNA N
OUTER COVER.....	CARBON STEEL
MEDIA.....	MELT BLOWN POLYPROPYLENE
OPERATING TEMPERATURE RANGE.....	-60 TO +250°F
AVAILABLE RATINGS.....	1/2, 1, 2, 5, 10 & 20 MICRONS

### **RECOMMENDED OPERATING LIMITS**

INITIAL PRESSURE DROP.....	< 2 PSI
RECOMMENDED CHANGE-OUT DELTA P.....	15 PSI
MAXIMUM FLOW, IRRESPECTIVE MAXIMUM ELEMENT OPERATING LIFE IRRESPECTIVE OF DIFFERENTIAL PRESSURE.....	1 YEAR

### **APPLICATION**

PERMIAN'S PPMP-4536 PLEATED ELEMENTS ARE SPECIALLY DESIGNED TO REPLACE PERMIAN PFG-336 STYLE FIBERGLASS ELEMENTS IN FILTER CASES SIMILAR TO THE PECO SERIES 70 AND 75, WHERE ESPECIALLY FINE FILTRATION IS DESIRED.